



Tel: (02) 9868 5055

Tel: (02) 9868 5063

Email: sales@globalvalves.com.au

Website: www.globalvalves.com.au









# EASY SET COLOUR CODED CAM

PROXIMITY SENSORS





MECHANICAL SWITCHES







FULLY ENCAPSULATED ASI CARD

INTERNALAL SOLENOID PILOT

M12 PLUG & SOCKET




INTEGRAL Solenoid

**Global Valves and Engineering Pty Ltd** 

"your partner for the future"

1100 SERIES 1200 SERIES


### **COMPOSITE WITH MECHANICAL SWITCHES COMPOSITE WITH PROXIMITY SENSORS**






1300 SERIES 1400 SERIES


ATEX FLAME PROOF SWITCH BOX **ALUMINIUM SWITCH BOX WITH BEACON INDICATOR** 








1500 SERIES 1600 SERIES **CONTROL STATION WITH INTEGRAL SOLENOID CONTROL STATION WITH BUS COMMUNICATION CARD** 








1800 SERIES **1900 SERIES**  **PUCK WITH PROXIMITY SENSORS PUCK WITH AS-I BUS COMMUNICATION** 



50mm



**Global Valves and Engineering Pty Ltd** 

## **NAMUR SOLENOID VALVES**

#### IP65, FLAME PROOF & INTRINSICALLY SAFE

5 port 2 position single coil 5 port 2 position double coil

5 port 3 position

Flow Rate: 1680 l/min @ 6 Bar Ports: 1/4\*BSP (NPT Optional)

Pressure range: 1.5 to 8 bar Maximum pressure: 10 bar

Voltages: 12, 24, 48 & 110 VDC

24, 48, 110 & 220 VAC



### **MAINFOLD SOLENOID VALVES**



#### IP65, FLAME PROOF & INTRINSICALLY SAFE

5 port 2 position single coil 5 port 2 position double coil

5 port 3 position

Size: 1/8" to 1/2"

Ports: BSP (NPT Optional)

Pressure range: 1.5 to 8 bar Maximum pressure:10 bar

Voltages: 12, 24, 48 & 110 VDC

24, 48, 110 & 220 VAC

## **PROXIMITY SENSORS**

#### **IP67 & INTRINSICALLY SAFE**

Output: PNP or NPN

NAMUR (I/S)

AC & DC two wire

Size: M12 to M30

with Plug & Socket



# LINEAR MOUNTING KITS



### **VALVE TYPES**

- Globe Valves
- Diaphragm Valves
- Control Valves
- Knife Gate Valves
- Gate Valves
- Pinch Valves

**Global Valves and Engineering Pty Ltd** 

"your partner for the future"