

# BRONZE SAFETY RELIEF VALVE

20-40 BAR \*RATED  
SIZE RANGE 15mm-50mm BSP M x F

Suitable for pressure relieving applications on Water, Steam, Air and Neutral Gases in Pulp & Paper, Power Generation, HVAC, Mining and other General Process Industries



## FEATURES

- Standard spring range 0.3 to 10 bar
- Suitable for use from -45 to 185 Deg C
- Bronze body
- Easing test lever
- Male inlet / female outlet
- Drip tight soft seated

## OPTIONS

- Fig. SRV dome type (without lever)
- Optional spring ranges 10-20 and 20-30 bar
- Fig. SRV-SS (stainless steel design)



Fig. SRV L



COMPONENT	MATERIAL
BODY	BRONZE
COVER	BRONZE
LEVER/SPRING	STEEL
SEAT/STEM/DISC	BRASS
CAP	CAST BRONZE
DISC INSERT	P.T.F.E.
BODY FINISH	SHOT BLAST

## DIMENSIONS

SIZE mm	15	20	25	32	40	50
A1	162	174	202	222	247	287
BORE Ø	13	19	25	32	38	50
*MAX PRESSURE kPa	4,000	4,000	4,000	3,000	3,000	2,000
FLOW RATE L/min @ ?P 700kPa	55	87	159	258	373	619
WT. KG	0.60	0.76	1.25	1.86	2.31	4.13

Data Sheet No. RV-SRV-L-Rev01

For installation, operation and maintenance refer to I.O.M.

Details subject to change

**Global Valves and Engineering Pty Ltd**

*"your partner for the future"*

Tel: (02) 9868 5055 Fax: (02) 9868 5063 Email: sales@globalvalves.com.au Website: www.globalvalves.com.au